

Data sheet

Commercial Art.No.: 92.232.4060.1

Cable assembly GST18i3K1BS 15H 40SW

GST18i3 connection cable female - male, length 4.0 m, 3 pole, coding mains 250 V, 16 A, coding color black, strain relief color black, cable color black, cross section 1.5 mm², cable type H05Z1Z1-F, fire class: Eca



Certificates / Approvals



Technical data

General

| | |
|--|----------------------------------|
| Rated current | 16 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 4 kV |
| Pollution degree | 2 |
| Mechanical coding | Code 1 |
| Lockable | self-locking (unlocking by tool) |
| Color of coding/ contact carrier | black |
| Marking of poles | L, N, PE |
| Color of housing inclusive strain relief | black |

Model

| | |
|---------------------------------|---------------------|
| Nominal cross section conductor | 1.5 mm ² |
| Degree of protection (IP) | IP20 |
| Cable type | H05Z1Z1-F |
| Cable colour | black |
| Cable diameter max. | 8 mm |
| Version of cable | Female - male |
| Type of cord set | Connecting cable |
| Version cable end 1 | GST18i3 female |
| Version cable end 2 | GST18i3 plug |

Material

| | |
|--|------------|
| Surface finish | Tin-plated |
| Halogen free | Yes |
| Continuous temperature of cable | 70 °C |
| Insulation components continuous temperature | 100 °C |
| Fire load | 1.673 kWh |
| Fire class | Eca |

Dimensions

| | |
|--------------|-----|
| Total length | 4 m |
|--------------|-----|

Classification

| | |
|------------|----------|
| ECLASS 8.1 | 27440604 |
| ETIM 7.0 | EC002587 |
| ETIM 6.0 | EC002587 |
| ETIM 5.0 | EC002587 |
| ETIM 4.0 | EC002587 |