
























ARMSTRONG TATRA

- Armstrong TATRA is a white classic fissured product
- Balanced acoustic solution with sound absorption $(0.55(H) \alpha_w)$ and sound attenuation (32 dB)



ARMSTRONG TATRA

Edge details Additional edge details on request	 Board 	Tegular 24 														
Thickness (mm)	 15	15														
Dimensions (mm) Additional sizes on request	 600 x 600 1200 x 600 1250 x 625	600 x 600														
System	 Exposed demountable - System C Exposed - Bandraster, demountable - System I.3 Exposed - Corridor, demountable - System F.3															
Weight	 3.6 - 3.8 kg / m ²															
Colour	 White															
Sound absorption	 EN ISO 354 $\alpha_w = \mathbf{0.55(H)}$ as per EN ISO 11654 - Class D <table border="1" data-bbox="467 969 1452 1041"> <thead> <tr> <th>Frequency <i>f</i> (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α_p</td> <td>0.40</td> <td>0.35</td> <td>0.50</td> <td>0.70</td> <td>0.75</td> <td>0.80</td> </tr> </tbody> </table> NRC = 0.55 as per ASTM C 423		Frequency <i>f</i> (Hz)	125	250	500	1000	2000	4000	α_p	0.40	0.35	0.50	0.70	0.75	0.80
Frequency <i>f</i> (Hz)	125	250	500	1000	2000	4000										
α_p	0.40	0.35	0.50	0.70	0.75	0.80										
Sound attenuation	 EN ISO 10848-2 $D_{n,f,w} = \mathbf{32\ dB}$ as per EN ISO 717-1															
Fire reaction	 Euroclass A2-s1, d0 as per EN 13501-1 RUS KM1 (G1, V1, D1, T1) as per FZ 123															
Light reflectance	 83%															
Thermal conductivity	 $\lambda = \mathbf{0.060\ W/m\ K}$ as per EN 12667															
Humidity resistance	 70% RH															
Indoor air quality	  A+  EN 13964 E1															
Cleanability	 															
Sustainability	 EN ISO 14621 37 - 48%  BIODEGRADABLE WOOL EC 1272/2008 Annex Q															

Products may vary from country to country. Please contact your local sales representative.
For further information and legal notice, please visit our website.