


Product code: 242915 EAN: 5901583242915

## LED line® downlight round adjustable die cast aluminium white



### Product description

Product coated with a matt paint finish which gives aesthetic appearance. Manufacturer issues a 5-year warranty for this product. Adjustable downlight fixture - the beam of light can be turned into any direction.



This product is suitable for recessed installation.



Adjustable downlight fixture - the beam of light can be turned into any direction.



Maximum suitable lamp power



Material (housing)



Type of surface suitable for installation



Mounting hole diameter

Name of the parameter	Value
Maximum suitable lamp power	35
IP protection rating	20
Warranty (years)	5
Colour	white
Fixture's diameter	92
Lamp's diameter	50
Material (housing)	DIE-CAST alu
Painting technique	Powder coated
Finish	matt
Y-axis angle regulation	45
Type of surface suitable for installation	F



Manufacturer issues a 5-year warranty for this product.



Product coated with a matt paint finish which gives aesthetic appearance.



IP protection rating



Y-axis angle regulation



Distance from illuminated surface



IEC protection class

Name of the parameter	Value
Distance from illuminated surface	0.5 m
Installation method	recessed
Mounting hole diameter	80 mm
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	100 pc
Height	30 mm
Master carton weight (kg)	10
Product code	242915

## Pre-packaging




Width [mm]	<b>100</b>
Height [mm]	<b>40</b>
Length [mm]	<b>100</b>
Weight [kg]	<b>0,0825</b>

## Cumulative packaging



Number of pieces	<b>100</b>
Width [mm]	<b>520</b>
Height [mm]	<b>420</b>
Length [mm]	<b>220</b>
Weight [kg]	<b>8,25</b>
Volume [m3]	<b>0,048048</b>

## Europallet



Number of pieces	<b>2100</b>
Bulk quantity	<b>21</b>
Weight [kg]	<b>173,25</b>
Weight [kg]	<b>173,25</b>
Pallet height [mm]	<b>1800</b>
Quantity in 1 layer	<b>7</b>
Number of layers	<b>3</b>